

panicLock AP4

Locking-switch-contact - VSK

winkhaus.com

Locking-switch-contact (VSK)

in combination with panicLock AP4 for building control or alarm system



3

2

1



Technical product description

The locking-switch-contact VSK is for monitoring the interlocking state, retrofittable for active and inactive panicLock AP4 locks. The combination of locking-switch-contact VSK with cable transition (e.g. with the sash part T-KÜ-T1-FT3,5M KONTAKT-AP4 VdS/IP67 and the usual cable transition - frame parts) is VdS class C tested and shows in the cable transition an IP67 protection (against water and dust) and easy-to-install twist-proof plugs for easy installation.



Acceptance

class C

No.: G 118050

Use

- monitoring of emergency exit and panic doors on single sash and double sash external doors
- optionally available as a supplement to panicLock AP4

Technical specifications VSK

Contact type:	changeover-contact
Switching voltage:	max. 30 V DC
Switching current::	max. 0,1 A
Cross section of wires:	3 x 0,14 mm ²
Wire assignment:	white = normally closed (NC) brown = joint contact (COM) green = normally open (NO)
Plug:	6-pole for wiring with T-KÜ-T1-FT 3,5M AP4 VDS / IP67
Protection classification:	IP 67
VdS:	class C
Environmental class:	III (according to VdS)
Ambient temperature:	-10°C ... +55°C
Screw fixing:	included screw for face plate mounting included

Description	Art.-No.
1 Sash part cable transition T-KÜ-T1-FT 3,5M KONTAKT-AP4 VDS / IP67 including 3,5 m cable and plug for Y-Kabel VSK DSK AP4	5061129
2 Frame part cable transition STV-KÜ-T1 RT Kabel 4M	5040503
3 Locking-switch-contact T-VERRIEGELUNGS-KONTAKT VSK AP4 0,2M, including screw DIN965 M2X10 PH1 A2F, plug-in	5061128

panicLock AP4

Handle-switch-contact - DSK

winkhaus.com

Handle-switch-contact (DSK)

in combination with panicLock AP4 for building control or alarm system



Technical product description

The handle-switch-contact DSK is used to monitor the handle status on the panic handle side (normally inside). The handle-switch-contact DSK can only be used in active and in special variants of panicLock AP4 (not retrofittable) e.g. T-SET AP4 E1 F1660/45S 92/9 M2 + DSK.

Use

- monitoring of emergency exit and panic doors on single sash and double sash external doors
- optionally available as a supplement to panicLock AP4
- DSK can be used both individually and together with locking-switch-contact VSK

Technical specifications DSK

Contact type::	normally open (NO)
Square:	9 mm
Switching voltage:	max. 28 V DC
Switching current:	max. 0,035 A
Wire:	2 x 0,14 mm ²
Wire assignment:	yellow = make contact grey = make contact
Screw fixing:	1 x screw DIN965 M2,5X8 PH1 A2F (included)

Description	Art.-No.
1 Sash part cable transition T-KÜ-T1-FT 3,5M KONTAKT-AP4 VDS / IP67 including 3,5 m cable and plug for Y-Kabel VSK DSK AP4	5061129
2 Frame part cable transition STV-KÜ-T1 RT Kabel 4M	5040503
3 T-Set AP4 E1 F(U)... 92/9 M2 + DSK including handle-switch-contact DSK, Y-Kabel VSK DSK AP4 such as screw DIN965 M2,5X8 PH1 A2F, e.g.	
T-SET AP4 E1 F1660/45S 92/9 M2+DSK	5061427
T-SET AP4 E1 F2060/55S 92/9 M2+DSK	5061428
T-SET AP4 E1 F2060/65S 92/9 M2+DSK	5061429
T-SET AP4 E1 U2460/35S 92/9 M2+DSK	5061426
Set consisting of:	
• Locking AP4 with modified main lock housing	
• Handle-switch-contact DSK	
• Y-KABEL VSK DSK AP4 with connection to handle-switch-contact DSK, locking-switch-contact VSK VdS AP4 with sash part cable transition T-KÜ-T1-FT 3,5M ... VdS / IP67 (other variants on request)	